

39 602

RAPID SL

SLX 2" X 6" IN-WALL CARRIER AND TANK FOR TOILET

Pure Freude
an Wasser



STANDARD SPECIFICATION:

- Dual Side channels for water connection and integrated power socket for shower toilets and bidet seats
 - Dual flush – 0.8gpf and 1.6gpf (3L and 6L)
 - Low noise operation – meets strict European noise (DIN) standards
 - No tools required for the installation of the inspection shaft including protection during construction phase, for vertical use
 - Self-supporting, pre-assembled powder coated steel frame with quick and lockable adjustments
 - ADA Compliant, bowl rim height adjustments from 15" to 19"
 - Pneumatic discharge valve offering 3 modes of operation: dual flush, start/stop or single flush
 - Tank insulated to prevent condensation
 - 2 fixing bolts included, 7- 9in (180-230mm) mounting screw distance
 - Small revision shaft included for small flush plates.
 - For use with 6 1/4" x 7 3/4" (156 x 197mm) flush plates, please order shaft 66 791 000 (sold separately)
 - 1/2" water supply connection from right, back or top
 - Inlet and outlet connecting set with fixed connections
 - Includes flow manager
- Actuation plate sold separately
 - 44" (1.13m) installation height
 - TÜV approved for load capacity
 - CALGreen compliant
 - WaterSense® compliant when paired with listed WaterSense® high efficiency compatible 0.8-1.28gpf (3-4.8lpf) wall hung toilet bowls
 - Includes integrated angle valve and push fit flexible hose union



PRODUCT FEATURES:

 GROHE Whisper®

 GROHE EcoJoy™

 GROHE QuickFix®

CERTIFICATIONS:



- ADA
- Massachusetts Plumbing Board Approved
- ASSE 1002
- CSA B45.15
- CSA B125.3
- CSA B125.12
- ASME A112.6.2
- ASME A112.19.5
- ASME A112.1002

AVAILABLE FINISHES:

39602000

NOTE: Install this product according to the installation guide. ADA, CSA compliant when installed to the specific requirements of these regulations.

We reserve the right to make revisions without notice to product specifications. 12-01-2021

US
Tel: 1.630.582.7711 Fax: 1.630.582.7722
For the most current Specification Sheet,
go to www.grohe.us.

Canada
Tel: 1.888.644.7643 Fax: 1.905.366.2071
For the most current Specification Sheet,
go to www.grohe.ca.

PART OF **LIXIL**

39 602

RAPID SL

SLX 2" X 6" IN-WALL CARRIER AND TANK FOR TOILET

Pure Freude
an Wasser



TECHNICAL DATA:

