

MT-116


1 Light MR16 Low Voltage Multiple Spot

WAC LIGHTING


Responsible Lighting®



6" x 6"



5 5/8" x 5 5/8"



PRODUCT DESCRIPTION

Square single light gimbal ring style adjustable recessed fixture, available with trim or Invisible Trim™, designed to sit flush with the ceiling for a clean, architectural look. Housing and trim ordered separately.

FEATURES

- Electronic short circuit and overload protection with automatic reset
- Soft start to prolong lamp life
- Trim version has a 1/4" low profile, Invisible Trim™ sits flush to ceiling
- The supplied clear glass lens can be replaced by a variety of lenses or accessories
- 25° vertical adjustment and 350° horizontal rotation
- 5 year WAC Lighting product warranty

TRIM ORDER NUMBER

Model #	Finish - Trim/Interior
MT-116 <i>(Order lamp separately)</i>	WT/WT White/White
MT-116LED <i>(7W 450lm LED MR16 included)</i>	

MT-116 - **WT/WT**

Example: **MT-116LED-WT/WT**

INVISIBLE TRIM™ ORDER NUMBER

Model #	Finish - Trim/Interior
MT-116TL <i>(Order lamp separately)</i>	WT White
MT-116LEDTL <i>(7W 450lm LED MR16 included)</i>	

MT-116 TL - **WT**

Example: **MT-116LEDTL-WT**

WAC Lighting
www.waclighting.com
Phone (800) 526.2588 • Fax (800) 526.2585

Headquarters/Eastern Distribution Center
44 Harbor Park Drive • Port Washington, NY 11050
Phone (516) 515.5000 • Fax (516) 515.5050

Western Distribution Center
1750 Archibald Avenue • Ontario, CA 91760
Phone (800) 526.2588 • Fax (800) 526.2585

Fixture Type:

Catalog Number:

Project:

Location:

SPECIFICATIONS

Construction: Stamped metal trim and aluminum housing. Frame, junction box and hanger bars are heavy gauge galvanized steel.

J-Box: Seven knockouts and four Romex® style wiring connectors provided for ease of installation. Rated for branch and chain wiring.

Transformer: Electronic, 120V AC input. Thermal protection provided to prevent against overheating and misuse of insulation near fixture.

Light Source: Accommodates most 12V LED MR16 or Halogen MR16 lamps (50W max).

Mounting: Supplied with hanger bars, adjustable from 15"-24½" to accommodate various joist construction and grid sizes. Accommodates surface of ½" to 1" thick. 5 3/16" x 5 3/16" cutout with trim, 5 5/8" x 5 5/8" cutout for Invisible Trim™.

Finish: *Trim version* - White Trim/White Interior (WT/WT). *Invisible Trim™* - White interior only.

Rating: Non-IC: Insulation must be kept at least 3" away from housing.

Standards: UL & CUL Listed. Suitable for damp locations.

HOUSING ORDER NUMBER

MT-116HS

